

MultiTac™ is a high quality PET film, coated on both sides with a pressure sensitive, high tack acrylic adhesive, one of which is protected by fine paper coated on both sides with siliconized PE. The adhesive is self-wound on the release liner. A clear and white version are available.

- SUITABLE FOR IMAGE DECAL AND HIGH-VOLUME MOUNTING OF GRAPHICS ONTO DIFFICULT SUBSTRATES, SUCH AS FOREX™, MDF, GATORBOARD™, ULTRABOARD™, FOAMEX™, OR SINTRA™
- THE WHITE VERSION OF MULTITAC™ OFFERS EXCELLENT OPACITY AND THE ABILITY TO MOUNT TO DARK SUBSTRATES

PRODUCT STRUCTURE

Adhesive	Acrylic (Pressure Sensitive)
Film	Clear PET or White PET
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 2 Side Siliconized Fine Paper

PRODUCT CHARACTERISTIC

Adhesive Layer	1.2 mil (30µ) on each side
Adhesive pH	6.0
180° Peel (ozf/in)	67
Service Temperature Range	-22°F to 284°F (-30°C to 140°C)
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

For more information,
performance and warranty
guidelines please contact your
local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013